



LYONNGREEN

INVERSORES



- ✓ Tiempo de transferencia cero para proteger cargas críticas como la misión servidores y cajeros automáticos.
- ✓ Módulo de control LCD extraíble con múltiples comunicaciones.
- ✓ Bluetooth incorporado para monitoreo móvil (Android Appis disponible).
- ✓ Soporta USB en la función.
- ✓ Puerto de comunicación reservado para BMS (RS485, CAN-BUS o RS232).
- ✓ Temporizador de uso de salida de CA / PV configurable y priorización.
- ✓ Operación paralela opcional de hasta 9 unidades.

MODEL	LYONNGREEN AP3000	LYONNGREEN AP5000
Rated Power	3000VA	5000VA
Parallel Capability	Up to 9 units	Up to 9 units
INPUT		
Voltage	220 VAC	
Voltage Range	110-280 VAC	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation	220 VAC \pm 5%	
Output THDv	<3% for linear load, <8% for non-linear load	
Surge Power	6000VA for 5 sec	10000VA for 5 sec
Efficiency (Peak)	93 % at Line Mode, 90% at Battery Mode	
Transfer	Time 0 ms	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC
Overcharge Protection	34 VDC	66 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	MPPT
Maximum PV Array Open Circuit Voltage	145 VDC	
Maximum PV Array Power	1500 W	4000 W
MPP Range @ Operating Voltage	30 ~ 115 VDC	60~115VDC
Maximum Solar Charge Current	60 A	80 A
Maximum AC Charge Current	60 A	60 A
Maximum Charge Current	120 A	140 A
PHYSICAL		
Dimension, D x W x H (mm)	140 x 303 x 525	
Net Weight (kgs)	13,0	13,5
Communication Interface	USB/RS232/RS485/Bluetooth/Dry-contact	
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operating Temperature	0°C to 55°C	
Storage Temperature	-15°C to 60°C	